

Label print in silk screen (from 1 to 6 Pantone colors)

Colors: Pantone C
Percentage: min.15% – max.85%. Black max.75%(total maximum inking: 300%)
Lines and points: min. thickness of the lines: 0.15 mm. Min. thickness of the points: 0.3 pt
Characters: Minimum 5 pt.
Graphical files : Provide us with high resolution PDF files, the images with min. 300dpi in CMYK colors (no RGB, Lab or indexed colors)

Label print with offset printing (from 1 to 6 colors)

Colors: Chart of color range Europe (CMYK)
Lines and points: min. thickness of the lines: 0.10 mm. Min. thickness of the points: 0.3 pt
Characters: Minimum 4 pt.
Graphical files : Provide us with high resolution PDF files, the images with min. 300dpi in CMYK colors (no RGB, Lab or indexed colors)

Label print in duplication

Graphical files : The graphical files have to be in the format 120x120 mm (format 1:1). The graphical elements can pass over the printing zone; the print driver will handle alignment. The files have to be in a high resolution of min. 300dpi and in CMYK mode or grayscale. If possible, please avoid large plain-colored full-surfaces.

Print of the printed matters in offset (from 1 to 4 colors)

Colors: Chart of color range Europe (CMYK) and Pantone C
Graphical files : Provide us with high resolution PDF files, the images with min. 300dpi in CMYK colors (no RGB, Lab or indexed colors)

The imposition of the pages have to be according to our specifications.

A binding color sample should be provided with the graphical files.